

ISOLATOR PROPERTIES									
ISOLATOR TYPE	Load Capacity (kg)	Load Capacity (lb)	Spring Color	AH-ORS Shore A Hardness					
AH-C-1A-7	7	15	Grey	40					
AH-C-1A-12	12	26	Green	40					
AH-C-1A-25	25	55	Blue	40					
AH-C-1A-50	50	110	Beige	50					
AH-C-1A-70	70	154	Red	50					
AH-C-1A-95	95	209	White	60					
AH-C-1A-140	140	309	Black	70					
AH-C-1A-185	185	408	Yellow	70					

NOTES:

THIS DRAWING IS PROPERTY OF ACREFINE ENGINEERING SERVICES LTD. IT CAN NOT BE COPIED OR DISTRIBUTED WITHOUT THE PERMISSION OF ACREFINE ENGINEERING SERVICES LTD. ® www.agefine

- Specified Load Capacity is the max. allowable load for a single isolator and this value must not be exceeded.
- 2. Isolator must be installed per Installation Instruction 9170.

POD PERFORMANCE OUTLINE DRAWING			AH-C-1A Type Combined Hanger with 1" Deflection	業	ACREFINE® FIXING & SEISMIC				
PROJECT	CUSTOMER		PROJECT NAME	DRAWING No.	8250		REV		
	ENGINEER			DRAWING BY	MMI	<u> </u>			
	DATE		LOCATION	DATE	16.12.2	020	U		
	PROJECT No.			SCALE	NTS	Page 1/	/2		